

Abrasive cloth, waterproof

CS 320 Y



Properties

Bonding agent	Resin
Grain	SiC
Coating	Close
Backing	Y-polyester

Product benefit

Outstanding abrasive performance on hard and difficult-to-machine materials - Ideal for high stress - Can be used wet or dry

Application

Glass/Stone	●
Mineral based materials	●
Plastic	●

Applications

- ▶ Wood processing industry
- ▶ Window and door construction
- ▶ Furniture industry

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
50 x 960	120	F4G butt joint	CS 320 Y	25	358965
50 x 1800	100	F4G butt joint	CS 320 Y	1	343836
75 x 637	60	F4G butt joint	CS 320 Y	20	343616
75 x 2000	24	F4G butt joint	CS 320 Y	1	343430
100 x 1800	60	F7G sine joint	CS 320 Y	1	343626
100 x 1800	80	F4G butt joint	CS 320 Y	1	343771

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de



Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
100 x 2215	120	F4G butt joint	CS 320 Y	1	343983
100 x 3350	80	F4G butt joint	CS 320 Y	1	351892
150 x 1800	24	F4G butt joint	CS 320 Y	1	361421
150 x 2260	80	F4G butt joint	CS 320 Y	1	359616
150 x 2620	80	F4G butt joint	CS 320 Y	1	359498

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

