Abrasive cloth, KULEX

CS 329 Y



Properties

Bonding agent	Resin
Grain	Al. oxide agglom.
Coating	Close
Backing	Y-polyester

Product benefit

Long-life abrasive belt for a satin surface scratch pattern, under low to medium grinding pressure - Especially suitable for dry grinding

Application

Stainless steel	●
Steel	●

Applications

- Stainless steel processing industry
- Pipeline construction
- Railing construction
- Apparatus and container manufacturing

Available grits:

16 24 30 36 40 50 60 **80** 100 **120** 150 **180** 220 **240** 280 **320** 360 **400** 500 **600** 800 1000 1200 1500 2000 2500 3000

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
970 x 1900	120	F4G butt joint	CS 329 Y	1	344558
970 x 1900	180	F4G butt joint	CS 329 Y	1	344562
970 x 1900	320	F4G butt joint	CS 329 Y	1	344569
970 x 1900	400	F4G butt joint	CS 329 Y	1	370777
1320 x 1900	80	F4G butt joint	CS 329 Y	1	359615

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de