

# Cutting-off wheel

# A 646 R SUPRA



Fe-S-Cl  
<0,1%



## Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■□
Aggression	■■■■■■■□
Service life	■■■■■■■□

## Product benefit

Free of iron, sulphur and chlorine - Universal use on steel and stainless steel - Cutting disc made of self-sharpening, calcined aluminum oxide - Tremendous aggressiveness when used for cutting solid steel materials

## Application

Steel	●
Stainless steel	○

## Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
125 x 1,6 x 22,23		80 m/s	12200 rpm	25	340946
150 x 1,6 x 22,23		80 m/s	10200 rpm	25	340945
180 x 1,6 x 22,23		80 m/s	8500 rpm	25	340944
230 x 1,9 x 22,23		80 m/s	6600 rpm	25	340943
230 x 1,9 x 22,23		80 m/s	6600 rpm	25	340942

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

